

# TRU TOUCH *RS* Series

## Redefine Smarter Collaboration

Let the versatile 4K UHD interactive display bring more collaboration and student engagement to your classroom. Turn the display into digital whiteboard, share files in one touch, and use your favorite software all with your fingers and the press of a button. TRU TOUCH RS works in your world and lets you interact your way.



### Dual user experience

for education and corporate users.

### Up to 20 points

of touch so multiple people can write and share ideas.

### Customizable UI

lets you be more productive, faster.

Model Name	TT-6518RS	TT-7518RS	TT-8618RS	TT-9818RS
Active Screen Size ("inch)	65"	75"	86"	98"
<b>DISPLAY</b>				
Backlight	LED			
Display Area	1429 x 804 mm	1650 x 928 mm	1895 x 1066 mm	2162 x 1217 mm
Display Ratio	16 : 9			
Resolution	3840 x 2160 Pixels (4K)			
Display Colors	8 bit		10 bit	
Brightness	370 cd/m2			500 cd/m2
Contrast Ratio	4000 : 1			
Life Time	> 30,000 hours			
<b>ELECTRICAL</b>				
Power Consumption	Maximum <220W Standby Mode ≤0.5W	Maximum <350W Standby Mode ≤0.5W	Maximum <450W Standby Mode ≤0.5W	Maximum <700W Standby Mode ≤0.5W
Working Voltage	AC 100-240V, 50/60Hz			
<b>TOUCH</b>				
Touch Surface	Next Generation Anti-Glare Glass			
Transparency	> 88%			
Haze	2% ~ 5%			
Touch Surface Hardness	> H7			
Touch Sensor	Infrared Touch			
Touch Points	20 Points Under Windows / 10 Points Under Android			
Touch Screen Writing Tools	Nano Pen / Finger / Palm			
Positioning Accuracy	± 2mm			± 3mm
Communication Interface	USB-A			
<b>SPEAKER</b>				
Speaker Position	Forward			
Rated Impedance	8Ω			
Freq. Response	200Hz - 20kHz			90Hz (±20%) - 18kHz
Max. Power Output	15W x 2			
Transmission Range	5M			
<b>TRANSPORTATION / STORAGE</b>				
Storage Temperature/Humidity	-20°C - 60°C / 20% - 90%			
Working Temperature/Humidity	0°C - 40°C / 20% - 80%			
Installation (Optional)	Wall-Mounted / Floor Stand			
Outline Dimension	1544 x 939 x 99 mm	1768 x 1066 x 104 mm	2019 x 1209 x 116 mm	2256 x 1361 x 106 mm
Net Weight	45 kg	59 kg	74 kg	130 kg
VESA Mount Installation Position	600 x 400 mm	800 x 400 mm		
Intelligent Thermal Protector	Automatic Hibernate when overheated			
Wireless Screen Sharing	Available			
<b>PORTS</b>				
Front Interface Inputs	HDMI 1.4 (4K@30Hz) x 1, USB (Touch) x 1, USB (Dynamic) x 2, MIC x 1			
Rear	AV Inputs	HDMI 2.0 (4K@60Hz) x 2, DP1.2 (4K@60Hz) x 1, VGA (1920x1080@60Hz) x 1, USB (Touch) x 4		
	AV Outputs	HDMI out x 1		
	Other	USB2.0 (Dynamic) x 1, USB3.0 (Dynamic) x 1, USB 2.0 Embedded x 1, RS232 x 1, RJ45 x 2, OPS Slots (4K@60Hz) x 1, DC 5V-2A Out, Line Out x 1, SPDIF Out x 1		

\* All specifications are subject to change without further notice.



**Newline Interactive Inc.**  
101 East Park Blvd. Suite 807  
Plano, TX 75074, USA  
TEL: +1 888 233 0868

**Want to buy:**  
info@newline-interactive.com  
**Become our partner:**  
partner@newline-interactive.com

**Europe office**  
Ronda de Poniente, N'2,  
1ª planta, Oficina 1B, 28760,  
Tres Cantos, Madrid, Spain  
TEL: +34 911169178

**Want to buy:**  
info\_eu@newline-interactive.com  
**Become our partner:**  
partner\_eu@newline-interactive.com

**Asia Pacific Office**  
4F-3, No.76 Sec.2, Jiafeng S. Rd,  
Zhubei City, Hsinchu Country,  
30272, Taiwan  
TEL: +886 35504768

**Want to buy:**  
info\_ap@newline-interactive.com  
**Become our partner:**  
partner\_ap@newline-interactive.com

**India office**  
Room No. 203, No. 37,  
TTK Road, Alwarpet, Chennai,  
Tamil Nadu, India, 600018  
TEL: +91 4446945513

**Want to buy:**  
info.in@newline-interactive.com  
**Become our partner:**  
partner.in@newline-interactive.com